

LIQUID-TUFF™

Low Smoke Zero Halogen – LSZH

UL Liquidtight Flexible Metal Conduit Type LFMC

Description


- Low smoke, zero halogen raceway
- Low toxicity generation characteristics
- Hot dipped zinc galvanized low carbon steel core
- Excellent temperature ratings
- Black thermoplastic polyurethane jacket
- UL bonding strip 3/8" – 1¼" for grounding
- Sunlight resistant
- Flame retardant TPU jacket

Temperature Rating

- 80°C/176°F Dry
- 60°C/140°F Wet
- 70°C/158°F Oil resistant
- -40°C/ 40°F Low temperatures

Applications

- Wherever limiting toxic material of combustion is needed
- Direct burial and concrete embedment
- Bond wire for grounding in sizes 3/8" – 1¼" NEC® 250.118(6)
- Hazardous Locations where Flexible Connections are required per NEC® 501.10(B)(2)(3), 502.10(A)(2)(2), 502.10(B)(2)(2), 503.10(A)(3)(2), 503.10(B), 504.20



References & Ratings

- UL 360 File E26540
- NEC® 250, 350, 390, 501.10(B)(2)(3), 502.10(A)(2)(2), 502.10(B)(2)(2), 503.10(A)(3)(2), 503.10(B), 504.20, 553.7(B), 600.31(A), 600.32(A)(1), 610.11(C), 620.21 (A)(1)(c)(2), 620.21(A)(2)(a), 620.21(A)(2)(d)(2), 620.21(A)(3)(a), 620.21(A)(3)(a), 620.21(A)(4)(2), 620.21(B)(1), 620.21(C)(1), 645.5(E)(2), 680.42(A)(1), 682.13, 690.31(A), 695.6(D) and 695.14(E)
- Department of Defense UL 360 adopted on October 1, 1987
- ASTM® E 162 Flame Spread Index
- ASTM® E 662 Smoke Density Generation
- Bombardier SMP-800C Toxic Gas Generation
- UL 94 Tests for Flammability of Plastic Materials for Parts
- UL does not list any manufacturers liquidtight conduit as low smoke zero halogen
- Made in USA of US and/or imported materials

Ordering Information Product Dimensions/Bend Radius

Product Code	Trade Size (inches)	Trade Size (mm)	Coil Length (feet)	Approx. Reel Length (feet)	Weight/100 feet (pounds)	External Diameter (inches)		Internal Diameter (min/max) inches	Bend Radius (inches)
						Over Jacket (min/max)			
6701-30-00	3/8	12	100'	—	24	0.690/0.710		0.484/0.504	2
6702-30-00	1/2	16	100'	—	31	0.820/0.840		0.622/0.642	3.25
6702-45-00	1/2	16	—	500'	31	0.820/0.840		0.622/0.642	3.25
6702-60-00	1/2	16	—	1000'	31	0.820/0.840		0.622/0.642	3.25
6703-30-00	3/4	21	100'	—	47	1.030/1.050		0.820/0.840	4.25
6703-45-00	3/4	21	—	500'	47	1.030/1.050		0.820/0.840	4.25
6703-60-00	3/4	21	—	1000'	47	1.030/1.050		0.820/0.840	4.25
6704-30-00	1	27	100'	—	78	1.290/1.315		1.041/1.066	6.5
6704-41-00	1	27	—	400'	78	1.290/1.315		1.041/1.066	6.5
6705-24-00	1¼	35	50'	—	102	1.630/1.660		1.380/1.410	8
6705-40-00	1¼	35	—	200'	102	1.630/1.660		1.380/1.410	8
6705-47-00	1¼	35	—	750'	102	1.630/1.660		1.380/1.410	8
6706-24-00	1½	41	50'	—	107	1.865/1.900		1.575/1.600	9
6707-24-00	2	53	50'	—	144	2.340/2.375		2.020/2.045	11.12
6708-22-00	2½	63	25'	—	168	2.840/2.875		2.480/2.505	14.62

NOTE: All dimensions and weights are subject to normal manufacturing tolerances.



3233 W Hunting Park Avenue, Philadelphia PA 19132-1845
 (800) 79-ROYAL (215) 221-1200 fax (215) 221-1201
 advisors@royalelectric.com www.royalelectric.com

WE GET IT
 24/7 Emergency Material Access

LIQUID-TUFF™

Low Smoke Zero Halogen – LSZH

UL Liquidtight Flexible Metal Conduit Type LFMC

Scope

This specification covers Kaf-Tech. LIQUID-TUFF™ LOW SMOKE ZERO HALOGEN (LSZH) UL Liquidtight Flexible Metal Conduit designed for use as a raceway for power, control and communication cables in accordance with Article 350 of the National Electric Code.

The product is intended for applications where limiting smoke and toxic materials of combustion are important considerations. The product is Underwriters Laboratories Inc. (UL) Listed for use at 80°C (176°F) in a dry location, 60°C (140°F) in a wet location and 70°C (158°F) in an oily location. It is also UL Listed for direct burial, outdoor use, sunlight resistance and for -40°C (-40°F) low temperatures applications. UL Listed Liquidtight Flexible Metal Conduit is manufactured and tested in accordance with Underwriters Laboratories Inc. Standard UL 360. The product carries the UL Listing Mark. Underwriters Laboratories Inc. does not list any manufacturers Liquidtight Flexible Metal Conduit as being low smoke zero halogen.

Construction

The LIQUID-TUFF™ LSZH Liquidtight Flexible Metal Conduit shall be formed from zinc coated galvanized low carbon steel strip having a uniform width and thickness. There shall be a continuous bonding strip built into the conduit core for the 3/8 through 1 1/4 trade sizes. The construction shall be in accordance with the UL 360 Standard. The Low Smoke Zero Halogen designation shall be based upon testing to ASTM® 162 – Flame Spread Index, ASTM® E662 – Smoke Density Generation and Bombardier SMP-800C – Toxic Gas Generation. The finished LIQUID-TUFF™ LSZH Liquidtight Flexible Metal Conduit dimensions shall be in accordance with Table 5.1 of UL 360 which is summarized in Table 3.

Jacket – TPU

A rugged low-smoke, moisture, oil, sunlight resistant and flame retardant thermoplastic polyurethane jacket shall be applied directly over the flexible metal conduit. The physical properties of the jacket material shall comply with the UL 360 Standard. The Low Smoke Zero Halogen jacket shall be tested to and comply with ASTM® 162 – Flame Spread Index, ASTM® E662 – Smoke Density Generation and Bombardier SMP-800C – Toxic Gas Generation. The test results are summarized in Table 1. Underwriters Laboratories Inc. (UL) does not list any manufacturers jacket compound as being low smoke zero halogen. The jacket wall thickness shall be in accordance with Table 4.1 of UL 360 which is summarized in Table 2. Jacket: Black

Grounding

Permanent circuit ground protection is provided through the continuous bonding strip built into the conduit core in trade sizes 3/8 through 1 1/4. A separate grounding conductor is required by the NEC® for all trade sizes 1 1/2 and larger.



Reference Standards

UL 360	Standard for Liquidtight Flexible Steel Conduit
File Reference	UL E26540
NEC® Articles	300.22, 350, 501.10(B)(2), 502.10(A)(2), 503.10(A)(2), 620.21(A)(1)(c)(2), 620.21(A)(2)(a), 620.21(A)(2)(d)(2), 620.21(A)(3)(a), 620.21(A)(4)(2), 620.21(B)(1), 620.21(C)(1) 645.5(E)(2), 680.21, 680.42, 695.6(E) and 695.14(E)
Department of Defense	UL 360 adopted on October 1, 1987
ASTM® E 162	Flame Spread Index
ASTM® E 662	Smoke Density Generation
Bombardier SMP-800C	Toxic Gas Generation
UL 94	Tests for Flammability of Plastic Materials for Parts

Markings

The surface of the outer jacket shall be clearly marked with a legible print legend in compliance with the UL 360 Standard.

Performance Tests

In accordance with UL 360, the completed LIQUID-TUFF™ LSZH Liquidtight Flexible Metal Conduit shall meet all of the performance requirements outlined in Appendix A.

LIQUID-TUFF™

Low Smoke Zero Halogen – LSZH

UL Liquidtight Flexible Metal Conduit Type LFMC

Table 1
LIQUID-TUFF™ LSZH Combustion and Flammability Properties

PROPERTY	TEST	RESULTS
Vertical Burn (Material)	UL 94	UL Listed: V-O Rating No Flaming Drips
Vertical Burn (Conduit)	UL 360	UL Listed: Passed
Oxygen Index % (Material)	ASTM® D 2863	25%
Flame Spread Index	ASTM® E-162	Passed No Flaming Drips
Smoke Generation (Flaming)	ASTM® E662 (NFPA-258)	Ds=13 @ 1.5 min Ds=57 @ 4.0 min No Flaming Drips
Smoke Generation (Non-flaming)	ASTM® E662 (NFPA-258)	Ds=1 @ 1.5 min Ds=8 @ 4.0 min No Flaming Drips
Toxic Gas Generation	Bombardier SMP-800C	Pass

Testing performed by independent test laboratory.
Test results available upon request.

Table 2
Jacket Thickness

Conduit Trade		Minimum Acceptable Average Thickness of Jacket, (inches)
Trade Size	Metric Designator	
3/8	12	0.030
1/2	16	0.030
3/4	21	0.035
1	27	0.035
1¼	35	0.035
1½	41	0.040
2	53	0.040
2½	63	0.050

Table 3
Conduit Diameters
Acceptable Internal and External Diameters

Conduit Size		Internal Diameter, In.		Over Jacket, In.	
Trade Size, In.	Metric Designator	Min.	Max.	Min.	Max.
3/8	12	0.484	0.504	0.690	0.710
1/2	16	0.622	0.642	0.820	0.840
3/4	21	0.820	0.840	1.030	1.050
1	27	1.041	1.066	1.290	1.315
1¼	35	1.380	1.410	1.630	1.660
1½	41	1.575	1.600	1.865	1.900
2	53	2.020	2.045	2.340	2.375
2½	63	2.480	2.505	2.840	2.875

Appendix A

UL 360 Performance Tests

Resistance and High Current
Fault Current
Impact
Tension
Crushing
Pipe Stiffness
Flexibility
Low Temperature Flexibility
Zinc Coating
Vertical Flame
Physical Properties
Deformation
Mechanical Water Absorption
Moisture Penetration
Sunlight Resistance
Test for Secureness of Fittings
Test for Durability of Ink Printing



3233 W Hunting Park Avenue, Philadelphia PA 19132-1845
(800) 79-ROYAL (215) 221-1200 fax (215) 221-1201
advisors@royalelectric.com www.royalelectric.com

WE GET IT
24/7 Emergency Material Access