


# UNISPLICE™ Replacement Splice

## UNISPLICE™

Replacement Tension Single Sleeve for ACSR, AAC, 6201, 5005 Compressed Conductors

Single sleeve aluminum UNISPLICE™ is designed to facilitate the replacement of existing line splices, including the automatic type. Utilizing all the benefits of the standard UNISPLICE™, the extra long Replacement UNISPLICE™ fills the gap of a cutout splice and eliminates



the need to find like conductor. It also reduces installation time of the current standard methods by half, reducing the total number of splices from two to one. All splices are prefilled with PENETROX™ joint compound and capped.



**ROYAL ELECTRIC SUPPLY COMPANY**  
Solutions Through Relationships—Since 1919

3233 W Hunting Park Avenue, Philadelphia PA 19132-1845  
(800) 79-ROYAL (215) 221-1200 fax (215) 221-1201  
advisors@royalelectric.com www.royalelectric.com

**WE GET IT**  
24/7 Emergency Material Access

Catalog Number	Conductor		L	Die Index	Installation Tooling Data (# of crimps per end)				
	AWG / kcmil	Str.			MD6 / MD7 HYTOOL™	Y35	Y750	Y45①	Y46②
YDSR4RL	4 ACSR 4 ACSR 4 6201 4 5005 4 AAC	6-1 7-1 7 7 7	24.63	BG 687 243	W-BG (12)* W687 (12)** W243 (12)	UBG (8)* U243 (6)	UBG (8) U243 (6)	UBG (8) U243 (6)	UBG (8) U243 (6)
YDSR2RL	2 ACSR 2 6201 2 5005 2 AAC	6-1; 7-1 7 7 7	28.00	BG 687 243	W-BG (20) W687 (10)** W243 (10)	UBG (8)* U243 (5)	UBG (8) U243 (5)	UBG (8) U243 (5)	UBG (8) U243 (5)
YDSR25RL	1/0 ACSR 1/0 6201 1/0 5005 1/0 AAC	6-1 7 7 7	34.13	C 167 247 660 702	WC (32) W247 (14) W660 (16) W702 (12)**	U167/U568 (14) U247 (7) U660 (8)	U167/U568 (14) U247 (7) U660 (8)	U167/U568 (14) U247 (7) U660 (8)	U167/U568 (14) U247 (7) U660 (8)
YDSR26RL	2/0 ACSR 2/0 6201 2/0 5005 2/0 AAC	6-1 7 7 7	35.50	659	-	U659 (Overlap Crimps)	U659 (Overlap Crimps)	U659 (Overlap Crimps)	U659 (Overlap Crimps)
YDSR27RL	3/0 ACSR 3/0 6201 3/0 5005 3/0 AAC	6-1 7 7 7	42.25	658	-	U658 (Overlap Crimps)	U658 (Overlap Crimps)	U658 (Overlap Crimps)	U658 (Overlap Crimps)
YDSR28RL	4/0 ACSR 4/0 6201 4/0 5005 4/0 AAC	6-1 7 7 7	45.75	654	-	U654 (Overlap Crimps)	U654 (Overlap Crimps)	U654 (Overlap Crimps)	U654 (Overlap Crimps)
YDSR321RL	336.4 ACSR 336.4 AAC 350.0 AAC	18-1 19 19	45.75	655	-	U655 (Overlap Crimps)	U655 (Overlap Crimps)	U655 (Overlap Crimps)	U655 (Overlap Crimps)
YDSR341RL	397.5 ACSR 419.6 5005	18-1 19	49.50	327	-	U327 (18)	U327 (18)	U327 (18)	U327 (18)
YDSR361RL	477.0 ACSR 556.5 ACSR 587.2 5005	18-1 18-1 19	51.25	788	-	U788 (Overlap Crimps)	U788 (Overlap Crimps)	U788 (Overlap Crimps)	U788 (Overlap Crimps)

①U die with PT-6515

②U die with PUAPD-1

\*Multiple crimp die set; makes more than one crimp per tool compression. Figure indicates number of compressions.

\*\*MD6 NON-BOW Dies produce straight sleeves without rotating tool