

MULTIOUTLET USB CHARGING

Plugmold® Multioutlet Systems are now available with multiple USB charging options that provide power and USB charging options for any application.

Choose from models with a single USB charging module and power receptacles, one with alternating USB charging modules and power receptacles, or an all USB charging module version.

Included tamper-resistant receptacles provide safety for multi-user facilities, residential living spaces and kitchens. Designed to easily mount on wall surfaces, the low-profile design is aesthetically pleasing and available in 3', 5' and 6' lengths in a variety of colors and finishes. Alternating USB/PWR available in 5' lengths only.

FEATURES & BENEFITS

- USB Charging Dual-port charging modules share 2.4 amps of charging capacity and can charge multiple phones, tablets or other mobile devices at the same time.
- Tamper-resistant receptacles Prevents the insertion of foreign objects into receptacles reducing the risk of shocks or electrocution. Meets 2014 NEC section 406 requirements.
- Multiple colors and finishes Choose from black or ivory ScuffCoat, white or gray painted enamel, or durable stainless steel finishes.
- Compact design. Low-profile design installs in tight locations while offering multiple power and USB charging connections. Receptacle spacing accommodates bulky AC adapters.



3233 W Hunting Park Avenue, Philadelphia PA 19132-1845 (800) 79-ROYAL (215) 221-1200 fax (215) 221-1201 advisors@royalelectric.com www.royalelectric.com

WE GET IT

24/7 Emergency Material Access



Length

[914mm]

[914mm]

[1.5m]

[1.8m]

[1.5m]

[1.8m]

[1.5m]

72" [1.8m]

[914mm]

[914mm]

[1.5m]

[1.8m]

[1.5m]

[1.8m]

[914mm]

[914mm]

60" [1.5m]

36"

60"

36"

72"

36"

60"

72"

36"

60"

36"

60"

72"

60"

72"

Finish

Plugmold with USB Module

Part Number

AL20GB306TRUSB

AL20GB506TRUSB

BK20GB306TRUSB

BK20GB506TRUSB

BK20GB606TRUSB

G20GB306TRUSB

G20GB506TRUSB

G20GB606TRUSB

S20GB306TRUSB

S20GB506TRUSB

S20GB606TRUSB

V20GB306TRUSB

V20GB506TRUSB

V20GB606TRUSB

WH20GB306TRUSB

WH20GB506TRUSB

WH20GB606TRUSB

PLUGMOLD® MULTIOUTLET SYSTEMS

Anodized Aluminum	
Anodized Aluminum	
Black Painted	
Black Painted	
Black Painted	
Gray Painted	
Gray Painted	
Gray Painted	
Stainless Steel	
Stainless Steel	
Stainless Steel	
Ivory Painted	
Ivory Painted	
Ivory Painted	
White Painted	
White Painted	
White Painted	

All USB Plugmold						
Part Number	Length		Finish	# of Modules		
AL20USB312	36"	[914mm]	Anodized Aluminum	3		
AL20USB512	60"	[1.5m]	Anodized Aluminum	5		
BK20USB312	36"	[914mm]	Painted Black	3		
BK20USB512	60"	[1.5m]	Painted Black	5		
G20USB312	36"	[914mm]	Painted Gray	3		
G20USB512	60"	[1.5m]	Painted Gray	5		
S20USB312	36"	[914mm]	Stainless Steel	3		
S20USB512	60"	[1.5m]	Stainless Steel	5		
V20USB312	36"	[914mm]	Painted Ivory	3		
V20USB512	60"	[1.5m]	Painted Ivory	5		
WH20USB312	36"	[914mm]	Painted White	3		
WH20USB512	60"	[1.5m]	Painted White	5		

Alternating USB-Power Receptacle Plugmold							
Part Number	Length	Finish	# of Modules				
AL20GB509TRUSBA	60" [1.5m]	Anodized Aluminum	3 Outlets & 3 USB Modules				
BK20GB509TRUSBA	60" [1.5m]	Black Painted	3 Outlets & 3 USB Modules				
G20GB509TRUSBA	60" [1.5m]	Gray Painted	3 Outlets & 3 USB Modules				
S20GB509TRUSBA	60" [1.5m]	Stainless Steel	3 Outlets & 3 USB Modules				
V20GB509TRUSBA	60" [1.5m]	Ivory Painted	3 Outlets & 3 USB Modules				
WH20GB509TRUSBA	60" [1.5m]	White Painted	3 Outlets & 3 USB Modules				





