



**Delivering 60.0A and 600V AC, water-tight and vibration-resistant Woodhead® Watertite™ Multi-Pin Plugs and Connectors are ideal for use in harsh-industrial outdoor and indoor applications**

**Features and Benefits**

600V; 30.0 and 60.0A current ratings	Supports high-power applications
Integrated molded design bonds cable to plug and connector with a solid neoprene rubber jacket	Ensures waterproof design and protects against dust. Provides one continuous insulation and protection jacket with no seams
Polarized connector	Prevents mis-mating
Spring-loaded solid brass sockets are wiped clean with every receptacle insertion	Provide maximum conductivity for long-term durability. Minimize heat buildup
Ground contact	Provides grounding safety at first-make-last-break (FMLB)
Removable pins (plug)	Allowing quick-disconnect access to fuses for field replacement
Drop-in replacement for Duraline* plugs and connectors	Provides a reliable second source with on time delivery dates

**Woodhead®  
Watertite™  
Heavy-Duty Molded  
Multi-Pin Plugs  
and Connectors**

**130150** 30.0A Rectangular Plugs and Connectors

**130155** 30.0 and 60.0A Circular Plugs and Connectors



30.0A Rectangular Plug and Connectors Series 130150



30.0 and 60.0A Circular Plug and Connectors Series 130155

\*Duraline is a trademark of J.B. Nottingham & Co., Inc.,

## Applications

### Manufacturing/Processing Facilities

- Ship Yards
- Food and Beverage Plants
- Manufacturing Plants
- Gas/Power/Water Processing Plants

### Municipal Intuitions

- Airports
- Subways
- Train and Bus Stations
- Hotels and Restaurants
- Wastewater Treatment Plants

### Entertainment

- Golf Courses
- Amusement Parks/Fairs/Zoos
- Aquariums

## Woodhead® Watertite™ Heavy-Duty Molded Multi-Pin Plugs and Connectors



Shipyard



Petrochemical Processing Facility



Beverage Processing Equipment

## Specifications

### Reference Information

Packaging: Bag  
Cable: MHSA approved

### Electrical

Voltage (max.): 600V AC  
Current (max.): 30.0 or 60.0A

### Physical

Housing: Neoprene  
Contact: Brass

## Ordering Information

Order No.	Engineering No.	Type	Interface	Gender	Current (Amps)	Cable Length (meters)	Cord Type	
<a href="#">130150-0320</a>	DW4M20	Plug	Rectangular	Male	30.0	1.83	8/4	
130150-0325	DW4F20	Connector		Female				
<a href="#">130155-0182</a>	DW730-30M	Plug	Round	Male		60.0	1.83	8/4
130155-0180	DW730-30F	Connector		Female				
130155-0183	DW730-30R	Connector		Female	N/A		N/A	
130155-0184	DW760-60F	Connector		Female	1.83		6/4	
130155-0185	DW760-60M	Plug		Male				
130155-0187	DW760-60R	Connector		Female	N/A		N/A	
130155-0192	DW760-60M38	Plug		Male	11.58		6/4	
130155-0186	DW760-60M75	Plug		Male	22.86		6/4	

[www.molex.com/link/watertitewetlocation.html](http://www.molex.com/link/watertitewetlocation.html)