

TYPE SSL

Flexible Stainless Steel Unjacketed Conduit

All Products Proudly Made in the USA



This non-UL, extra-flexible, unjacketed, stainless steel conduit is available in the smaller diameters, and designed for corrosive environments, as well as tight-spot installations.

Construction:

- Continuously spiral wound and squarelocked 304L stainless steel.
- Also available in 316L stainless steel, minimum order quantities will apply.

Application:

- Offers excellent resistance to corrosive environments.
- Extra flexible for tight bend applications.
- Intended for use with various set screw or clamp type connectors.


Product Information

CERTIFICATIONS & COMPLIANCE



WEEE and RoHS Compliant

Squarelock:



Product Table: *SSL is priced per ft. & is available in custom lengths; consult factory for pricing and minimum runs.

US Trade Size	Type	Internal Diameter		Outer Diameter		Inside Bend Radius (IN.)	Approx. Weight per 100 ft.
		MIN (IN.)	MAX (IN.)	MIN (IN.)	MAX (IN.)		
	SSL-316	0.172	0.202	0.280	0.310	0.75	4.4
	SSL-140	0.235	0.265	0.328	0.358	0.75	5.6
5/16"	SSL-516	0.297	0.327	0.391	0.421	0.75	6.8
	SSL-380	0.360	0.390	0.485	0.515	1.00	8.0
	SSL-716	0.422	0.452	0.547	0.577	1.00	11.1
3/8"	SSL-10	0.493	0.512	0.617	0.637	1.00	12.5
	SSL-916	0.547	0.577	0.672	0.702	1.25	13.9
1/2"	SSL-11	0.622	0.642	0.747	0.767	1.50	15.3
	SSL-340	0.735	0.765	0.865	0.895	1.50	18.1
3/4"	SSL-12	0.827	0.847	0.957	0.977	2.00	24.0
1"	SSL-13	1.041	1.066	1.191	1.216	2.00	27.3
1 1/4"	SSL-14	1.380	1.410	1.540	1.570	3.00	-
1 1/2"	SSL-15	1.575	1.600	1.735	1.770	3.50	-
2"	SSL-16	2.020	2.045	2.180	2.215	3.50	75.3
2 1/2"	SSL-17	2.500	2.545	2.680	2.715	4.50	-
3"	SSL-18	3.000	3.045	3.180	3.215	5.50	158.0

For more information, contact us at 215-221-1200 or advisors@royalelectric.com